



FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 7/5/2022 Revision date: 7/5/2022 Supersedes version of: 9/24/2015 Version: 1.6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION
Product code : PRU101, PRU201
Other means of identification : UPC 78072700170

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use
Use of the substance/mixture : Polishes and wax blends.
Function or use category : Cleaning/washing agents and additives

1.2.2. Uses advised against

Restrictions on use : This material should not be used for any other purpose than the identified uses without expert advice. Improper use may cause potential health, safety and environmental risks.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Farecla Products Limited
Broadmeads
Ware, SG12 9HS – Hertfordshire
UK

T +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday) - F +44 (0)19 2046 T 0033 (0) 4 90 85 85 00 - F 0033 (0) 4 90 82 94 52
6557

technical@farecla.com - www.farecla.com

Only Representative

Saint-Gobain Coating Solutions
50 rue du Mourelet Z.I. Courtine Moure Frais, B.P.
FR- 90966 84093 Avignon – Cedex
France

qualite-ehs.coating-solutions@saint-gobain.com

1.4. Emergency telephone number

Emergency number : +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not Classified

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH210 - Safety data sheet available on request. EUH208 - Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
Child-resistant fastening	: Not applicable
Tactile warning	: Not applicable

Nordic countries regulation

Denmark

MAL code : 00-1

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 – 30	Asp. Tox. 1, H304
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 64742-48-9 EC-No.: 918-481-9 REACH-no: 01-2119457273-39	1 – 10	Asp. Tox. 1, H304

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-Aminoethanol	CAS-No.: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8 REACH-no: 01-2119486455-28	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1, H314 Eye Dam. 1, H318 Aquatic Chronic 2, H411
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Skin Sens. 1, H317 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Acute 1, H400
Sodium Nitrate	CAS-No.: 7631-99-4 EC-No.: 231-554-3 REACH-no: 01-2119488221-41	< 0.003	Ox. Sol. 3, H272 Eye Irrit. 2, H319
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 STOT RE 1, H372 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

Specific concentration limits:

Name	Product identifier	Specific concentration limits
2-Aminoethanol	CAS-No.: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8 REACH-no: 01-2119486455-28	(5 ≤C < 100) STOT SE 3, H335
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	(0.05 ≤C ≤ 100) Skin Sens. 1, H317
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤C < 0.6) Skin Irrit. 2, H315 (0.06 ≤C < 0.6) Eye Irrit. 2, H319 (0.6 ≤C ≤ 100) Skin Corr. 1C, H314 (0.6 ≤C ≤ 100) Eye Dam. 1, H318

Comments

: Contains amongst other ingredients:
5-15% aliphatic hydrocarbons; 5-15% zeolites; <5% nonionic surfactants, polycarboxylates, perfume, colourant, chloromethylisothiazolinone, methylisothiazolinone, benzisothiazolinone. For more ingredient information visit www.farecla.com

Full text of H- and EUH-statements: see section 16

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Contact during a long period may cause light irritation. Itching.
Symptoms/effects after eye contact	: May cause eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not scatter spilled material with high-pressure water streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Unidentified organic compounds may be formed in fumes and smoke during combustion.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Precautionary measures fire	: Evacuate area.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. Stop leak if safe to do so. Clean up any spills as soon as possible, using an absorbent material to collect it.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up liquid spill into absorbent material. Absorb spilled material with sand or earth. Shovel or sweep up and put in a closed container for disposal. Clean contaminated surfaces with an excess of water.
-------------------------	---

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep at temperatures above freezing. Allowing freezing conditions may degrade product.
Incompatible products : Strong acids. Oxidizing agent.
Incompatible materials : Oxidizers (strong).
Information on mixed storage : Store away from foodstuffs.
Storage area : Store away from heat. Store in a well-ventilated place.

7.3. Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Switzerland - Occupational Exposure Limits

Local name	Distillats légers de pétrole, hydrotraités (vapeurs) / Destillate (Erdöl), mit Wasserstoff behandelte, leichte (Dampf)
MAK (OEL TWA) [1]	350 mg/m ³
MAK (OEL TWA) [2]	50 ppm (vapour)
KZGW (OEL STEL)	700 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm (vapour)
Critical toxicity	SNC / ZNS
Notation	SS _c / SS _c
Remark	OSHA
Regulatory reference	www.suva.ch, 01.01.2021

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Austria - Occupational Exposure Limits

MAK (OEL TWA)	0.05 mg/m ³ (5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one mixture in ratio 3:1)
OEL chemical category	Skin sensitizer

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SSc / S, SSc
Regulatory reference	www.suva.ch, 01.01.2021

Sodium Nitrate (7631-99-4)

Czech Republic - Occupational Exposure Limits

PEL (OEL TWA)	6 mg/m ³ (dust)
---------------	----------------------------

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

Poland - Occupational Exposure Limits

Local name	Benzyna do lakierów
NDS (OEL TWA)	300 mg/m ³
NDSCh (OEL STEL)	900 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286

Switzerland - Occupational Exposure Limits

Local name	Naphta lourd (pétrole), hydrotraité / Naphtha (Erdöl), mit Wasserstoff behandelte, schwere
MAK (OEL TWA) [1]	300 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	600 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm
Critical toxicity	SNC / ZNS
Regulatory reference	www.suva.ch, 01.01.2021

2-Aminoethanol (141-43-5)

EU - Indicative Occupational Exposure Limit (IOEL)

IOEL TWA	2.5 mg/m ³
IOEL TWA [ppm]	1 ppm
IOEL STEL	7.6 mg/m ³
IOEL STEL [ppm]	3 ppm
Remark	Possibility of significant uptake through the skin

Austria - Occupational Exposure Limits

MAK (OEL TWA)	2.5 mg/m ³
MAK (OEL TWA) [ppm]	1 ppm
MAK (OEL STEL)	7.6 mg/m ³
MAK (OEL STEL) [ppm]	3 ppm

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
OEL chemical category	Skin sensitizer
Belgium - Occupational Exposure Limits	
Local name	Ethanolamine # Ethanolamine
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
OEL chemical category	Skin, Skin notation
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Етаноламин (2-Аминоетанол)
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	2.5 mg/m ³
GVI (OEL TWA) [2]	1 ppm
KGVI (OEL STEL)	7.6 mg/m ³
KGVI (OEL STEL) [ppm]	3 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
Local name	2-Aminoethanol (Ethanolamin)
PEL (OEL TWA)	2.5 mg/m ³

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
PEL (OEL TWA) [ppm]	1 ppm
NPK-P (OEL C)	7.5 mg/m ³
NPK-P (OEL C) [ppm]	3 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
OEL TWA [1]	2.5 mg/m ³
OEL TWA [2]	1 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
Local name	2-Aminoetanoli
HTP (OEL TWA) [1]	2.5 mg/m ³
HTP (OEL TWA) [2]	1 ppm
HTP (OEL STEL)	7.6 mg/m ³
HTP (OEL STEL) [ppm]	3 ppm
Remark	Iho
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Ethanolamine (2-Aminoéthanol)
VME (OEL TWA)	2.5 mg/m ³
VME (OEL TWA) [ppm]	1 ppm
VLE (OEL C/STEL)	7.6 mg/m ³
VLE (OEL C/STEL) [ppm]	3 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
OEL chemical category	Risk of cutaneous absorption
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA) [1]	0.5 mg/m ³
AGW (OEL TWA) [2]	0.2 ppm
Peak exposure limitation factor	1(I)

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; Sh - Hautsensibilisierender Stoff; H - hautresorptiv; 11 - Summe aus Dampf und Aerosolen
Chemical category	Skin notation, Skin sensitization
Regulatory reference	TRGS900
Gibraltar - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
Local name	Αιθανολαμίνη (2-αμινοαιθανόλη)
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	skin - potential for cutaneous absorption
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	2.5 mg/m ³
CK (OEL STEL)	7.6 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
Local name	2-Aminoethanol [Ethanolamine]
OEL TWA [1]	2.5 mg/m ³
OEL TWA [2]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Chemical Agents Code of Practice 2021
Italy - Occupational Exposure Limits	
Local name	2-Amminoetanolo

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
Remark	Cute
OEL chemical category	skin - potential for cutaneous absorption
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia - Occupational Exposure Limits	
OEL TWA	0.5 mg/m ³
OEL TWA [ppm]	0.2 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	2.5 mg/m ³
IPRV (OEL TWA) [ppm]	1 ppm
TPRV (OEL STEL)	7.6 mg/m ³
TPRV (OEL STEL) [ppm]	3 ppm
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
Local name	2-Aminoethanol
TGG-8u (OEL TWA)	2.5 mg/m ³
TGG-15min (OEL STEL)	7.6 mg/m ³
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2022

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
Poland - Occupational Exposure Limits	
Local name	2-Aminoetanol
NDS (OEL TWA)	2.5 mg/m ³
NDSCh (OEL STEL)	7.5 mg/m ³
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³ (indicative limit value)
OEL TWA [ppm]	1 ppm (indicative limit value)
OEL STEL	7.6 mg/m ³ (indicative limit value)
OEL STEL [ppm]	3 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	2.5 mg/m ³
NPHV (OEL TWA) [2]	1 ppm
NPHV (OEL C)	7.6 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	2.5 mg/m ³
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m ³
OEL STEL [ppm]	3 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
Local name	2-Aminoetanol (Etanolamina)
VLA-ED (OEL TWA) [1]	2.5 mg/m ³
VLA-ED (OEL TWA) [2]	1 ppm
VLA-EC (OEL STEL)	7.5 mg/m ³
VLA-EC (OEL STEL) [ppm]	3 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
OEL chemical category	skin - potential for cutaneous absorption
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Etanolamin
NGV (OEL TWA)	2.5 mg/m ³
NGV (OEL TWA) [ppm]	1 ppm
KTV (OEL STEL)	7.5 mg/m ³
KTV (OEL STEL) [ppm]	3 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
OEL chemical category	Skin notation
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	2-Aminoethanol
WEL TWA (OEL TWA) [1]	2.5 mg/m ³
WEL TWA (OEL TWA) [2]	1 ppm
WEL STEL (OEL STEL)	7.6 mg/m ³
WEL STEL (OEL STEL) [ppm]	3 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
WEL chemical category	Potential for cutaneous absorption
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Norway - Occupational Exposure Limits	
Local name	2-aminoetanol (Etanolamin)
Grenseverdi (OEL TWA) [1]	2.5 mg/m ³
Grenseverdi (OEL TWA) [2]	1 ppm
Korttidsverdi (OEL STEL)	5 mg/m ³ (value calculated)
Korttidsverdi (OEL STEL) [ppm]	2 ppm (value calculated)
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grenseverdi og/eller anmerkning for stoffet.
OEL chemical category	Skin notation
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	2-Aminoéthanol / 2-Aminoethanol [Ethanolamin]
MAK (OEL TWA) [1]	5 mg/m ³
MAK (OEL TWA) [2]	2 ppm
KZGW (OEL STEL)	10 mg/m ³
KZGW (OEL STEL) [ppm]	4 ppm
Critical toxicity	Peau, Fatigue, Yeux / Haut, Fatigue, Auge
Notation	S / S

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)	
Remark	NIOSH
OEL chemical category	Sensitizer
Regulatory reference	www.suva.ch, 28.03.2022
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Safety glasses.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Hand protection:

Protective gloves. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl").

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.

8.2.2.4. Thermal hazards

No additional information available

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Purple.
Odour	: pleasant.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: ≈ 0 °C
Boiling point	: > 100 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: Not available
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 7.5 – 8.5
Viscosity, kinematic	: 10000 mm ² /s (20°C)
Viscosity, dynamic	: 10000 cP (20°C)
Solubility	: Dispersible in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: 1
Relative vapour density at 20 °C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 176 g/l (18.06%)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong oxidizers. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not Classified
Acute toxicity (dermal) : Not Classified
Acute toxicity (inhalation) : Not Classified

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

1,2-benzisothiazol-3(2H)-one (2634-33-5)

LD50 oral rat	490 mg/kg bodyweight
LD50 oral	670 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LD50 oral rat	66 mg/kg bodyweight
LD50 dermal rat	> 141 mg/kg bodyweight
LC50 Inhalation - Rat	0.17 mg/l air

Sodium Nitrate (7631-99-4)

LD50 oral rat	3430 mg/kg bodyweight
LD50 oral	3700 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

2-Aminoethanol (141-43-5)

LD50 oral rat	1720 mg/kg
LD50 dermal rabbit	1000 mg/kg
LD50 dermal	1018 mg/kg

Skin corrosion/irritation : Not Classified
pH: 7.5 – 8.5

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sodium Nitrate (7631-99-4)	
pH	7
2-Aminoethanol (141-43-5)	
pH	12.1 Temp.: 20 Concentration: 100 g/L
Serious eye damage/irritation	: Not Classified pH: 7.5 – 8.5
Sodium Nitrate (7631-99-4)	
pH	7
2-Aminoethanol (141-43-5)	
pH	12.1 Temp.: 20 Concentration: 100 g/L
Respiratory or skin sensitisation	: Not Classified
Germ cell mutagenicity	: Not Classified
Carcinogenicity	: Not Classified
Reproductive toxicity	: Not Classified
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
STOT-single exposure	: Not Classified
STOT-repeated exposure	: Not Classified
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Sodium Nitrate (7631-99-4)	
NOAEL (oral, rat, 90 days)	≥ 1500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
2-Aminoethanol (141-43-5)	
NOAEL (oral, rat, 90 days)	300 mg/kg bodyweight Animal: rat, Guideline: other:OECD Guideline 416 (Two-generation reproduction toxicity study)
Aspiration hazard	: Not Classified
FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION	
Viscosity, kinematic	10000 mm ² /s (20°C)
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
Hydrocarbon	Yes
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
Viscosity, kinematic	1.8 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'
2-Aminoethanol (141-43-5)	
Viscosity, kinematic	23.392 mm ² /s

11.2. Information on other hazards

No additional information available

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not Classified
Hazardous to the aquatic environment, long-term (chronic)	: Not Classified
Not rapidly degradable	

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

LC50 - Fish [1]	2.2 mg/l
-----------------	----------

1,2-benzisothiazol-3(2H)-one (2634-33-5)

LC50 - Fish [1]	2.18 mg/l
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0.11 mg/l
ErC50 algae	150 µg/l

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.007 mg/l
EC50 - Crustacea [2]	0.0052 mg/l (Skeletonema costatum) (OECD 201)
EC50 72h - Algae [1]	0.048 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'
NOEC chronic crustacea	0.004 mg/l 21 d (Daphnia) (OECD 211)
NOEC chronic algae	0.0012 mg/l 72 h (Pseudokirchneriella subcapitata) (OECD 201)

Sodium Nitrate (7631-99-4)

LC50 - Fish [1]	> 100 mg/l
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	8609 mg/l

2-Aminoethanol (141-43-5)

LC50 - Fish [1]	349 mg/l Test organisms (species): Cyprinus carpio
LC50 - Fish [2]	3684 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 - Crustacea [1]	65 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	2.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2-Aminoethanol (141-43-5)

EC50 72h - Algae [2]	2.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	2.5 mg/l
NOEC (chronic)	0.85 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	1.24 mg/l Test organisms (species): Oryzias latipes Duration: '41 d'

12.2. Persistence and degradability

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Persistence and degradability	Rapidly biodegradable.
-------------------------------	------------------------

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Persistence and degradability	No persistence data available for this product.
-------------------------------	---

12.3. Bioaccumulative potential

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Bioaccumulative potential	No indication of bio-accumulation potential.
---------------------------	--

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Partition coefficient n-octanol/water (Log Kow)	6 – 8.2
---	---------

1,2-benzisothiazol-3(2H)-one (2634-33-5)

BCF - Fish [1]	6.62
----------------	------

Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99
---	-------------

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

BCF - Fish [1]	41 – 54
----------------	---------

Bioconcentration factor (BCF REACH)	3.6 (calculated) S 1177
-------------------------------------	-------------------------

Partition coefficient n-octanol/water (Log Pow)	0.75
---	------

Sodium Nitrate (7631-99-4)

Partition coefficient n-octanol/water (Log Pow)	-3.8
---	------

2-Aminoethanol (141-43-5)

Partition coefficient n-octanol/water (Log Pow)	-1.91 (at 25 °C)
---	------------------

Partition coefficient n-octanol/water (Log Kow)	-1.31
---	-------

12.4. Mobility in soil

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Ecology - soil	Readily absorbed into soil.
----------------	-----------------------------

1,2-benzisothiazol-3(2H)-one (2634-33-5)

Surface tension	72.6 mN/m
-----------------	-----------

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97
--	------

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1
--	----------

12.5. Results of PBT and vPvB assessment

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 08 04 12 - adhesive and sealant sludges other than those mentioned in 08 04 11

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(b)	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics ; 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; 2-Aminoethanol
3(c)	5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone ; 2-Aminoethanol

REACH Annex XIV (Authorisation List)

Contains no REACH Annex XIV substances

REACH Candidate List (SVHC)

Contains no substance on the REACH candidate list

PIC Regulation (Prior Informed Consent)

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

POP Regulation (Persistent Organic Pollutants)

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Ozone Regulation (1005/2009)

Contains no substance subject to REGULATION (EU) No 1005/2009 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 September 2009 on substances that deplete the ozone layer.

VOC Directive (2004/42)

VOC content : 176 g/l (18.06%)

Explosives Precursors Regulation (2019/1148)

Contains substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Sodium nitrate	7631-99-4	3102 50 00	ex 3824 99 96

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on drug precursors)

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

Listed on ELINCS (European List of Notified Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on the Canadian DSL (Domestic Substances List)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on the United States TSCA (Toxic Substances Control Act) inventory

France

Occupational diseases	
Code	Description
RG 49	Skin disorders caused by aliphatic, alicyclic amines or ethanolamines
RG 49 BIS	Respiratory disorders caused by aliphatic amines, ethanolamines or isophoronediamine
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 10/12 - Liquids

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
SDS	Safety Data Sheet

Full text of H- and EUH-statements:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.

FARECLA PROFILE CARNAUBA UV WAX HAND APPLICATION

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Ox. Sol. 3	Oxidising Solids, Category 3
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

While Farecla Products Ltd. believes that the data and information contained herein are factual and the opinions are those of qualified experts, they are not to be taken as a warranty or representation for which Farecla assumes any legal responsibility. They are offered solely for the consideration, investigation, data and information in accordance with applicable laws and regulations.