

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 1 of 12

Print date: 07/02/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Impermax ST
Product Code: P241
UFI: 5Y00-F0W2-400W-3MTR

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Coating

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **KRYPTON CHEMICAL SL**
Address: Martí i Franquès 12. Pol. Ind. les Tàpies
City: 43890 l'Hospitalet de l'Infant
Province: Spain
Telephone: +34 977 822 245
Fax: +34 977 823 977
E-mail: rayston@kryptonchemical.com
Web: www.kryptonchemical.com

1.4 Emergency telephone number: +34 977 822 245 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Flam. Liq. 3 : Flammable liquid and vapour.

Resp. Sens. 1 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves/protective clothing/eye protection/face protection
P284 [In case of inadequate ventilation] wear respiratory protection.
P342+P311 Call a POISON CENTER/doctor if you feel unwell.
P370+P378 In case of fire: Use anti-alcohol foam, chemical or dry powder, carbonic anhydride for extinction.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 2 of 12

Print date: 07/02/2024

EUH statements:

EUH208 Contains 4,4'diphenylmethane diisocyanate, oligomers. May produce an allergic reaction.

Contains:

Aromatic polyurethane polymer

2.3 Other hazards.

The mixture does not contain substances classified as PBT.

The mixture does not contain substances classified as vPvB.

The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 96328-90-4	Aromatic polyurethane polymer	1 - 75 %	Resp. Sens. 1, H334 - Skin Sens. 1, H317	-
Index No: 607-195-00-7 CAS No: 108-65-6 EC No: 203-603-9 Registration No: 01-2119475791-29-XXXX	[1] 2-methoxy-1-methylethyl acetate	2.5 - 10 %	Flam. Liq. 3, H226 - STOT SE 3, H336	-
Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	1 - 10 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	1 - 10 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-
CAS No: 25686-28-6 EC No: 500-040-3 Registration No: 01-2119457013-49	4,4'diphenylmethane diisocyanate, oligomers	<0.1 %	Acute Tox. 4, H332 - Carc. 2, H351 - Eye Irrit. 2, H319 - Resp. Sens. 1, H334 - Skin Irrit. 2, H315 - Skin Sens. 1, H317 - STOT RE 2, H373 - STOT SE 3, H335	-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 3 of 12

Print date: 07/02/2024

Index No: 607-251-00-0 CAS No: 70657-70-4 EC No: 274-724-2	2-methoxypropyl acetate	0 - 0.3 %	Flam. Liq. 3, H226 - Repr. 1B, H360D *** - STOT SE 3, H335	-
--	-------------------------	-----------	--	---

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

* *** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

It may cause an allergic reaction in the respiratory system. Chronic exposure can lead to asthma.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. If the person vomits, clear the respiratory tract. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

During a fire and depending on its magnitude the following may occur:

- Flammable vapors or gases.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 4 of 12

Print date: 07/02/2024

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product not classified as hazardous for the environment, avoid spillage as much as possible.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.

The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.

Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 ° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

Classification and threshold amount of storage in accordance with Annex I to Directive 2012/18/EU (SEVESO III):

Code	Description	Qualifying quantity (tonnes) for the application of	
		Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5.000	50.000

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 5 of 12

Print date: 07/02/2024

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
2-methoxy-1-methylethyl acetate	108-65-6	European Union [1]	Eight hours	50 (skin)	275 (skin)
			Short term	100 (skin)	550 (skin)
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
ethylbenzene	100-41-4	European Union [1]	Eight hours	100 (skin)	442 (skin)
			Short term	200 (skin)	884 (skin)

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	DNEL (Workers)	Inhalation, Chronic, Systemic effects	275 (mg/m ³)
	DNEL (Consumers)	Inhalation, Chronic, Systemic effects	33 (mg/m ³)
	DNEL (Workers)	Dermal, Chronic, Systemic effects	153,5 (mg/kg bw/day)
	DNEL (Consumers)	Dermal, Chronic, Systemic effects	54,8 (mg/kg bw/day)
	DNEL (Consumers)	Oral, Chronic, Systemic effects	1,67 (mg/kg bw/day)
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
2-methoxy-1-methylethyl acetate CAS No: 108-65-6 EC No: 203-603-9	aqua (freshwater)	0,635 (mg/L)
	aqua (marine water)	0,0635 (mg/L)
	aqua (intermittent releases)	6,35 (mg/L)
	STP	100 (mg/L)
	sediment (freshwater)	3,29 (mg/kg sediment dw)
	sediment (marine water)	0,329 (mg/kg sediment dw)
	soil	0,29 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration: 100 %

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST






Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 6 of 12

Print date: 07/02/2024

Uses:	Coating				
Breathing protection:					
PPE:	Filter mask for protection against gases and particles.				
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.				
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Filter Type needed:	A2				
Hand protection:					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
PPE:	Protective goggles with built-in frame.				
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.				
CEN standards:	EN 165, EN 166, EN 167, EN 168				
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.				
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.				
Skin protection:					
PPE:	Anti-static protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.				
PPE:	Anti-static safety footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346				
Maintenance:	The footwear should be checked regularly				
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Depending on pigmentation

Odour: Solvent

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: n.d. °C

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 238 °C

Flammability: flammable

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 7 of 12

Print date: 07/02/2024

Lower explosion limit: n.d.
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: 45 °C
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: n.a.
Kinematic viscosity: nd
Solubility: Organic solvents
Hydrosolubility: not soluble
Liposolubility: nd
Partition coefficient n-octanol/water (log value): nd
Vapour pressure: nd
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 1,3
Relative vapour density: nd
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Information with regard to physical hazard classes

Explosives:

Explosive properties: non explosive

Flammable liquids:

Sustained combustibility: Yes.

Oxidising liquids:

Oxidizing properties: non oxidant

Other safety characteristics

Viscosity: 5000-10000 cps 25°C

Dropping point: n,d,

Blink: n,d,

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

Flammable liquid and vapour.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
2-methoxy-1-methylethyl acetate	Oral	LD50	Rat (female)	8532 mg/kg bw [1]
	Dermal	LD50	Rabbit	>5000 mg/kg bw [1]
	Inhalation	LC0	Rat	>4345 ppm (6 h) [1]
CAS No: 108-65-6	EC No: 203-603-9			

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 8 of 12

Print date: 07/02/2024

xylene	Oral	LD50	Rata/Rat	4300 mg/kg bw [1]
	Dermal	LD50	Rabbit/ Conejo	> 1700 mg/kg bw [1]
	Inhalation	LC50	Rat/Rata	21,7 mg/l/4 h [1]
CAS No: 1330-20-7	EC No: 215-535-7			
ethylbenzene	Oral	LD50	Rat	3500 mg/kg bw [1]
	Dermal	LD50	Rabbit	15400 mg/kg bw [1]
	Inhalation			
CAS No: 100-41-4	EC No: 202-849-4			
4,4'diphenylmethane diisocyanate, oligomers	Oral	LD50	Rat, female	>5000 mg/kg [1]
	Dermal			
	Inhalation			
CAS No: 25686-28-6	EC No: 500-040-3			

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 12.421 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Product classified:

Respiratory sensitiser, Category 1: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Based on available data, the classification criteria are not met.

g) reproductive toxicity;

Based on available data, the classification criteria are not met.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity			
	Type	Test	Kind	Value
2-methoxy-1-methylethyl acetate	Fish	LC50	Oryzias latipes	100 mg/L (96 h) [1]
	Aquatic	EC50 (24	Daphnia magna	407 mg/L (48 h) [1]

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 9 of 12

Print date: 07/02/2024

CAS No: 108-65-6 EC No: 203-603-9	invertebrates	h)		
	Aquatic plants	EC50	Selenastrum capricornutum (Pseudokirchnerella subcapitata)	>1000 mg/L (72 h) [1]
CAS No: 1330-20-7 EC No: 215-535-7	Fish	LC50	Fish	15.7 mg/l (96 h) [1]
	Aquatic invertebrates	LC50	Crustacean	8,5 mg/l (48 h) [1]
	Aquatic plants			
CAS No: 25686-28-6 EC No: 500-040-3	Fish	LC50	Brachydanio rerio	>1000 mg/l (96h) [1]
	Aquatic invertebrates	EC50	Daphnia magna	>1000 mg/l (24h) [1]
	Aquatic plants	EC50	Desmodium subspicatus	>1640 mg/l (72) [1]

12.2 Persistence and degradability.

Information about biodegradability:

Name	Biodegradability				
	Conditions	Initial conc.	% degradation	Parameter	Period
4,4'diphenylmethane diisocyanate, oligomers CAS No: 25686-28-6 EC No: 500-040-3	Anaerobic Method: Inherent Biodegradability: Modified MITI Test (II)	30 mg/l	0		28 d

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019
Version 1083 (replaces version 1082) Revision date: 15/04/2020

Page 10 of 12
Print date: 07/02/2024

Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions
Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading
Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN1866

14.2 UN proper shipping name.

Description:
ADR/RID: UN 1866, RESIN SOLUTION, 3, PG III, (E)
IMDG: UN 1866, RESIN SOLUTION, 3, PG III (45°C)
ICAO/IATA: UN 1866, RESIN SOLUTION, 3, PG III

14.3 Transport hazard class(es).

Class(es): 3

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: No
Transport by ship, FEM – Emergency sheets (F – Fire, S - Spills): F-E,S-E

14.6 Special precautions for user.

Labels: 3



Hazard number: Not applicable.
Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Proceed in accordance with point 6.
ADR LQ: 5 L
IMDG LQ: 5 L
ICAO LQ: 10 L

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): i - One-pack performance coatings, solvent-borne

Phase I* (from 01/01/2007): 600 g/l

Phase II* (from 01/01/2010): 500 g/l

(*) g/l ready to use

VOC content (p/p): 15 %

VOC content: 184 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019

Version 1083 (replaces version 1082)

Revision date: 15/04/2020

Page 11 of 12

Print date: 07/02/2024

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.(órganos de audición)

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Asp. Tox. 1 : Aspiration toxicity, Category 1
Carc. 2 : Carcinogen, Category 2
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Repr. 1B : Reproductive toxicant, Category 1B
Resp. Sens. 1 : Respiratory sensitiser, Category 1
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR/RID: Agreement concerning the International Carriage of Dangerous Goods by Road.

CEN: European Committee for Standardization.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

EC50: Half maximal effective concentration.

PPE: Personal protection equipment.

IATA: International Air Transport Association.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P241-Impermax ST

Version 1 Date of compilation: 26/08/2019
Version 1083 (replaces version 1082) Revision date: 15/04/2020

Page 12 of 12
Print date: 07/02/2024

ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.