

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 1 of 13

Print date: 13/09/2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: Impermax Cold Polyurea Supreme Comp.A
Product Code: P117
UFI: STD0-A04U-E006-DR7N

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Paint and/or related product.

Uses advised against:

Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company: **KRYPTON CHEMICAL SL**
Address: Martí i Franquès 12. Pol. Ind. les Tàpies
City: 43890 l'Hospitalet de l'Infant
Province: Spain
Telephone: +34 977 822 245
Fax: +34 977 823 977
E-mail: rayston@kryptonchemical.com
Web: www.kryptonchemical.com

1.4 Emergency telephone number: +34 977 822 245 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Eye Irrit. 2 : Causes serious eye irritation.

Skin Sens. 1 : May cause an allergic skin reaction.

STOT RE 2 : May cause damage to organs through prolonged or repeated exposure if inhaled.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Warning

Hazard statements:

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P260 Do not breathe mist or vapours.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection

P321 Specific treatment (see supplemental first aid instructions on this label)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 2 of 13

Print date: 13/09/2024

P362+P364 Take off contaminated clothing and wash it before reuse.
P391 Collect spillage.
P501 Dispose of the content or container in (In accordance with local, regional, national or international regulations)

EUH statements:

EUH208 Contains bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate. May produce an allergic reaction.
EUH208 Contains methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction.
EUH208 Contains Fatty acids, C14-18 and C16-18-unsatd., maleated. May produce an allergic reaction.

Contains:
maleic anhydride
diethylmethylbenzenediamine

2.3 Other hazards.

The mixture does not contain substances classified as PBT.
The mixture does not contain substances classified as vPvB.
The mixture does not contain any endocrine disrupting properties substances.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
Index No: 612-130-00-0 CAS No: 68479-98-1 EC No: 270-877-4 Registration No: 01-2119486805-25-XXXX	diethylmethylbenzenediamine	10 - 25 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - STOT RE 2 *, H373 **	-
CAS No: 41556-26-7 EC No: 255-437-1	bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.25 - 1 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Skin Sens. 1, H317	-
CAS No: 85711-46-2 EC No: 288-306-2	Fatty acids, C14-18 and C16-18-unsatd., maleated	0.1 - 1 %	Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 82919-37-7 EC No: 280-060-4	methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	0.1 - 0.25 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Skin Sens. 1, H317	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 3 of 13

Print date: 13/09/2024

Index No: 601-022-00-9 CAS No: 1330-20-7 EC No: 215-535-7 Registration No: 01-2119488216-32-XXXX	[1] xylene	0 - 0.2 %	Acute Tox. 4 *, H312 - Acute Tox. 4 *, H332 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 601-023-00-4 CAS No: 100-41-4 EC No: 202-849-4 Registration No: 01-2119489370-35-XXXX	[1] ethylbenzene	0 - 0.1 %	Acute Tox. 4 *, H332 - Asp. Tox. 1, H304 - Flam. Liq. 2, H225 - STOT RE 2, H373(órganos de audición)	-
Index No: 606-005-00-X CAS No: 108-83-8 EC No: 203-620-1 Registration No: 01-2119474441-41-XXXX	2,6-dimethylheptan-4-one, di-isobutyl ketone	0 - 0.1 %	Flam. Liq. 3, H226 - STOT SE 3, H335	STOT SE 3, H335: C ≥ 10 %
Index No: 607-096-00-9 CAS No: 108-31-6 EC No: 203-571-6 Registration No: 01-2119472428-31-XXXX	maleic anhydride	0.001 - 1 %	Acute Tox. 4, H302 - Eye Dam. 1, H318 - Resp. Sens. 1, H334 - Skin Corr. 1B, H314 - Skin Sens. 1A, H317 - STOT RE 1, H372	Skin Sens. 1A, H317: C ≥ 0,001 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a European Union exposure limit in the workplace (see section 8.1).

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance. Don't let the person to rub the affected eye.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 4 of 13

Print date: 13/09/2024

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 °C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 5 of 13

Print date: 13/09/2024

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
xylene	1330-20-7	European Union [1]	Eight hours	50 (skin)	221 (skin)
			Short term	100 (skin)	442 (skin)
ethylbenzene	100-41-4	European Union [1]	Eight hours	100 (skin)	442 (skin)
			Short term	200 (skin)	884 (skin)

[1] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
diethylmethylenediamine CAS No: 68479-98-1 EC No: 270-877-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	0,13 (mg/m ³)
xylene CAS No: 1330-20-7 EC No: 215-535-7	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)
ethylbenzene CAS No: 100-41-4 EC No: 202-849-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	77 (mg/m ³)
2,6-dimethylheptan-4-one, di-isobutyl ketone CAS No: 108-83-8 EC No: 203-620-1	DNEL (Workers)	Inhalation, Chronic, Local effects	290 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	479 (mg/m ³)
maleic anhydride CAS No: 108-31-6 EC No: 203-571-6	DNEL (Workers)	Inhalation, Chronic, Local effects	0,4 (mg/m ³)
	DNEL (Workers)	Inhalation, Chronic, Systemic effects	0,4 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %
Uses:	Paint and/or related product.
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.



-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 6 of 13

Print date: 13/09/2024

Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.		
Filter Type needed:	A2		
Hand protection:			
PPE:	Protective gloves against chemicals.		
Characteristics:	«CE» marking, category III.		
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420		
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.		
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.		
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480
		Material thickness (mm):	0,35
Eye protection:			
PPE:	Protective goggles with built-in frame.		
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.		
CEN standards:	EN 165, EN 166, EN 167, EN 168		
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.		
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.		
Skin protection:			
PPE:	Protective clothing.		
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.		
CEN standards:	EN 340		
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.		
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.		
PPE:	Work footwear.		
Characteristics:	«CE» marking, category II.		
CEN standards:	EN ISO 13287, EN 20347		
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.		
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

Physical state: Liquid

Colour: Not applicable/Not available due to the nature/properties of the product

Odour: Not applicable/Not available due to the nature/properties of the product

Odour threshold: Not applicable/Not available due to the nature/properties of the product

Melting point: Not applicable/Not available due to the nature/properties of the product

Freezing point: Not applicable/Not available due to the nature/properties of the product

Boiling point or initial boiling point and boiling range: 763 °C (Estimation based on the indication of the Regulation (CE) N°1272/2008.)

Flammability: Not applicable/Not available due to the nature/properties of the product

Lower explosion limit: Not applicable/Not available due to the nature/properties of the product

Upper explosion limit: Not applicable/Not available due to the nature/properties of the product

Flash point: >100 °C

Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product

Decomposition temperature: Not applicable/Not available due to the nature/properties of the product

pH: Not applicable/Not available due to the nature/properties of the product

Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 7 of 13

Print date: 13/09/2024

Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: 0,011 (Estimation based on the indication of the Regulation (CE) N°1272/2008.)
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 1.32 g/cm³
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information

Other safety characteristics

Viscosity: 2200 mPa.s (25°C)

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Splashes in the eyes can cause irritation.

11.1 Information on hazard classes as defined in Regulation (EC) N° 1272/2008.

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

Toxicological information about the substances present in the composition.

Name	Acute toxicity			
	Type	Test	Kind	Value
diethylmethylbenzenediamine CAS No: 68479-98-1 EC No: 270-877-4	Oral	DL50 [1] OECD TG 401	Rat	738 mg/kg [1]
	Dermal	DL50 [1] OECD TG 402	Rat	>2000 mg/kg [1]
	Inhalation			
xylene	Oral	LD50 [1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956	Rata/Rat	4300 mg/kg bw [1]
	Dermal	LD50 [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974	Rabbit/Cone jo	> 1700 mg/kg bw [1]
	Inhalation	LC50	Rat/Rata	21,7 mg/l/4 h [1]

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 8 of 13

Print date: 13/09/2024

CAS No: 1330-20-7	EC No: 215-535-7		[1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 123, 1974
ethylbenzene		Oral	LD50 Rat 3500 mg/kg bw [1]
		Dermal	[1] AMA Archives of Industrial Health. Vol. 14, Pg. 387, 1956
			LD50 Rabbit 15400 mg/kg bw [1]
	Inhalation	[1] Food and Cosmetics Toxicology. Vol. 13, Pg. 803, 1975	
CAS No: 100-41-4	EC No: 202-849-4		

a) acute toxicity;

Not conclusive data for classification.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 13.884 mg/kg

ATE (Oral) = 5.123 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Product classified:

Eye irritation, Category 2: Causes serious eye irritation.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitizer, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Not conclusive data for classification.

f) carcinogenicity;

Not conclusive data for classification.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Product classified:

Specific target organ toxicity following a repeated exposure, Category 2: May cause damage to organs through prolonged or repeated exposure if inhaled.

j) aspiration hazard;

Based on available data, the classification criteria are not met.

11.2 Information on other hazards.

Endocrine disrupting properties

This product does not contain components with endocrine-disrupting properties with effects on human health.

Other information

There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

Name	Ecotoxicity
------	-------------

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 9 of 13

Print date: 13/09/2024

	Type	Test	Kind	Value
diethylmethylbenzenediamine CAS No: 68479-98-1 EC No: 270-877-4	Fish	CL50 [1] DIN 38412 Part 15	Leuciscus idus	200 mg/l (48h) [1]
	Aquatic invertebrates	CE50 [1] OECD TG 202	Daphnia magna	0.5 mg/l (48h) [1]
	Aquatic plants	CE50r [1] OECD TG 201	Desmodesmus subspicatus	104 mg/l (72h) [1]
xylene CAS No: 1330-20-7 EC No: 215-535-7	Fish	LC50 [1] Bailey, H.C., D.H.W. Liu, and H.A. Javitz 1985. Time/Toxicity Relationships in Short-Term Static, Dynamic, and Plug-Flow Bioassays. In: R.C.Bahner and D.J.Hansen (Eds.), Aquatic Toxicology and Hazard Assessment, 8th Symposium, ASTM STP 891, Philadelphia, PA :193-212	Fish	15.7 mg/l (96 h) [1]
	Aquatic invertebrates	LC50 [1] Tatem, H.E., B.A. Cox, and J.W. Anderson 1978. The Toxicity of Oils and Petroleum Hydrocarbons to Estuarine Crustaceans. Estuar.Coast.Mar.Sci. 6(4):365-373. Tatem, H.E. 1975. The Toxicity and Physiological Effects of Oil and Petroleum Hydrocarbons on Estuarine Grass Shrimp Palaemonetes pugio (Holthuis). Ph.D.Thesis, Texas A&M University, College Station, TX :133 p	Crustacean	8,5 mg/l (48 h) [1]
	Aquatic plants			

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present.

No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

No information is available regarding the bioaccumulation of the substances present.

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.

This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 10 of 13

Print date: 13/09/2024

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.

Land: Transport by road: ADR, Transport by rail: RID.

Transport documentation: Consignment note and written instructions

Sea: Transport by ship: IMDG.

Transport documentation: Bill of lading

Air: Transport by plane: ICAO/IATA.

Transport document: Airway bill.

14.1 UN number or ID number.

UN No: UN3082

14.2 UN proper shipping name.

Description:

ADR/RID: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DIETHYLMETHYLBENZENEDIAMINE / BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE), 9, PG III, (-)

IMDG: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DIETHYLMETHYLBENZENEDIAMINE / BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE), 9, PG III, MARINE POLLUTANT

ICAO/IATA: UN 3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (CONTAINS DIETHYLMETHYLBENZENEDIAMINE / BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE), 9, PG III

14.3 Transport hazard class(es).

Class(es): 9

14.4 Packing group.

Packing group: III

14.5 Environmental hazards.

Marine pollutant: Yes



Dangerous for the environment

Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-A,S-F

14.6 Special precautions for user.

Labels: 9



Hazard number: 90

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.

Proceed in accordance with point 6.

ADR LQ: 5 L

IMDG LQ: 5 L

ICAO LQ: 30 kg B

14.7 Maritime transport in bulk according to IMO instruments.

The product is not transported in bulk.

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 11 of 13

Print date: 13/09/2024

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

Volatile organic compound (VOC)

Product Subcategory (Directive 2004/42/EC): j - Two-pack reactive performance coatings for specific end use such as floors, solvent-borne

Phase I* (from 01/01/2007): 550 g/l

Phase II* (from 01/01/2010): 500 g/l

(*) g/l ready to use

VOC content (p/p): 0,6 %

VOC content: 7,6 g/l

The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles:

Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
<p>3. Liquid substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008:</p> <p>(a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F;</p> <p>(b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10;</p> <p>(c) hazard class 4.1;</p> <p>(d) hazard class 5.1.</p>	<p>1. Shall not be used in:</p> <ul style="list-style-type: none">- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,- tricks and jokes,- games for one or more participants, or any article intended to be used as such, even with ornamental aspects, <p>2. Articles not complying with paragraph 1 shall not be placed on the market.</p> <p>3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:</p> <ul style="list-style-type: none">- can be used as fuel in decorative oil lamps for supply to the general public, and,- present an aspiration hazard and are labelled with H304, <p>4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).</p> <p>5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:</p> <p>(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';</p> <p>(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';</p> <p>(c) lamp oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.</p>

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 12 of 13

Print date: 13/09/2024

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.(órganos de audición)
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Dermal), Category 4
Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Dam. 1 : Serious eye damage, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Resp. Sens. 1 : Respiratory sensitiser, Category 1
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1A : Skin sensitiser, Category 1A
STOT RE 1 : Specific target organ toxicity following a repeated exposure, Category 1
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 3 : Specific target organ toxicity following a single exposure, Category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2020/878)

P117-Impermax Cold Polyurea Supreme Comp.A

Version 1 Date of compilation: 2/08/2021

Version 16 (replaces version 15)

Revision date: 18/04/2024

Page 13 of 13

Print date: 13/09/2024

PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2020/878.

Regulation (EC) No 1907/2006.

Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.