

SAFETY DATA SHEET

RESION EP Coving Mortar Base

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

RESION EP Coving Mortar Base

Product no.

FS901

Unique formula identifier (UFI) MRE0-R0T4-T00V-HSYY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Binder

Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 12	Manufacture of plastics products, including compounding and conversion
SU 19	Building and construction work
Product category	Description
PC 9b	Fillers, putties, plasters, modelling clay
PC 32	Polymer Preparations and Compounds
Process category	Description
Process category PROC 19	Description Hand-mixing with intimate contact and only PPE available
	-
PROC 19	Hand-mixing with intimate contact and only PPE available
PROC 19 Article category	Hand-mixing with intimate contact and only PPE available Description
PROC 19 Article category AC 13 Environmental	Hand-mixing with intimate contact and only PPE available Description Plastic articles
PROC 19 Article category AC 13 Environmental release category	Hand-mixing with intimate contact and only PPE available Description Plastic articles Description
PROC 19 Article category AC 13 Environmental release category ERC 5	Hand-mixing with intimate contact and only PPE available Description Plastic articles Description Industrial use resulting in inclusion into or onto a matrix

EuPCS

PC / Chemical products (excludes biocidal products)

PC-ADH-2 / Adhesives and sealants - building and construction works (except cement based adhesives)

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Polyestershoppen BV Oostbaan 680 2841 ML Moordrecht Netherlands



+31 85 0220090

Contact person

E-mail

info@polyestershoppen.nl

Revision 23/11/2023

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Skin Irrit. 2; H315, Causes skin irritation. Skin Sens. 1; H317, May cause an allergic skin reaction. Eye Irrit. 2; H319, Causes serious eye irritation. Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word Warning

Hazard statement(s)

Causes skin irritation. (H315) May cause an allergic skin reaction. (H317) Causes serious eye irritation. (H319) Harmful to aquatic life with long lasting effects. (H412)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101) Keep out of reach of children. (P102)

Prevention

Avoid breathing mist/vapour. (P261) Wash hands thoroughly after handling. (P264) Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352) If skin irritation or rash occurs: Get medical advice/attention. (P333+P313)

Storage

-

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

bis-[4-(2,3-epoxipropoxi)phenyl]propane oxirane, mono[(C12-14-alkyloxy)methyl] derivs. Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane



Additional labelling

EUH205, Contains epoxy constituents. May produce an allergic reaction. UFI: MRE0-R0T4-T00V-HSYY

2.3. Other hazards

Additional warnings

Contains epoxy constituents. May produce an allergic reaction.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
bis-[4-(2,3- epoxipropoxi)phenyl]propane	CAS No.: 1675-54-3 EC No.: 216-823-5 UK-REACH: Index No.: 603-073-00-2	15-25%	Skin Irrit. 2, H315 (SCL: 5.00 %) Skin Sens. 1, H317 Eye Irrit. 2, H319 (SCL: 5.00 %) Aquatic Chronic 2, H411	
oxirane, mono[(C12-14- alkyloxy)methyl] derivs.	CAS No.: 68609-97-2 EC No.: 271-846-8 UK-REACH: Index No.: 603-103-00-4	3-5%	Skin Irrit. 2, H315 Skin Sens. 1, H317	[19]
Reaction mass of 2,2'- [methylenebis(2,1- phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1- phenyleneoxymethylene)]bis(oxirane) and 2-{{2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}m ethyl)oxirane	CAS No.: EC No.: 701-263-0 UK-REACH: Index No.:	3-5%	EUH205 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.



If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas. Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.



SECTION 7: Handling and storage

7.1. Precautions for safe handling

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage material

Keep only in original packaging.

Storage temperature

Dry, cool and well ventilated

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Quartz (SiO2) Long term exposure limit (8 hours) (mg/m³): 0,1 (respirable fraction) Annotations: Carc = Capable of causing cancer and/or heritable genetic damage.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	0.0893 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	0.75 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	0.87 mg/m3
Long term – Systemic effects - Workers	Inhalation	4.93 mg/m3
Short term – Systemic effects - General population	Oral	0.5 mg/kg bw/day

PNEC

bis-[4-(2,3-epoxipropoxi)phenyl]propane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater	Single	0.006 mg/L
Freshwater sediment	Single	0.341 mg/kg
Marine water	Single	0.001 mg/L
Marine water sediment	Single	0.034 mg/kg
Sewage treatment plant	Single	10 mg/L
Soil	Single	0.065 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.



General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Apply standard precautions during use of the product. Avoid inhalation of vapours.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Туре	Class	Colour	Standards	
No special when usec as intended.	3			
Skin protection				
Recommended	Type/Category	Standards		
Dedicated work clothing should be worn.	-	-		R
Hand protection				
Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	
Eye protection				

Type Standards Safety glasses with side EN166 shields. Image: Control of the second se

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Highly viscous mass

Colour Gray

Odour / Odour threshold Characteristic



рΗ

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

Testing not relevant or not possible due to the nature of the product.

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C) >100

Flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water Slightly soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.



10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	15000 mg/kg
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	23000 mg/kg
Product/substance Species: Route of exposure: Test: Result:	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane Rat Oral LD50 >5000 mg/kg
Product/substance Species: Route of exposure: Test: Result:	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane Rat Dermal LD50 >2000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.



Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Quartz (SiO2) has been classified by IARC as a group 1 carcinogen. bis-[4-(2,3-epoxipropoxi)phenyl]propane has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

Product/substance Species:	bis-[4-(2,3-epoxipropoxi)phenyl]propane Fish
Duration:	96 hours
Test:	LC50
Result:	2 mg/L
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Daphnia
Duration:	48 hours
Test:	EC50
Result:	1.8 mg/L
Product/substance	bis-[4-(2,3-epoxipropoxi)phenyl]propane
Species:	Algae
Duration:	72 hours
Test:	EC50
Result:	11 mg/L
Product/substance	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane
Test method:	OECD 201
Species:	Algae, Pseudokirchneriella subcapitata
Test:	EC50
Result:	>1,8 mg/L
Product/substance	Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'- [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxirane
Test method:	OECD 211
Species:	Crustacean, Daphnia magna
Test:	NOEC
Result:	0,3 mg/L
Harmful to aquatic li	fe with long lasting effects.
2.2 Persistence and d	egradability

12.2. Persistence and degradability No data available.

12.3. Bioaccumulative potential

Product/substanceReaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and [methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2- ylmethoxy)benzyl]phenoxy}methyl)oxiranePotential bioaccumulation:No data available.LogPow:3,6BCF:No data available.	12			
LogPow: 3,6		Product/substance		
5		Potential bioaccumulation:	No data available.	
BCF: No data available.		LogPow:	3,6	
		BCF:	No data available.	



12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (*) HP 4 - Irritant (skin irritation and eye damage) HP 13 – Sensitising HP 14 – Ecotoxic Dispose of contents/container to an approved waste disposal plant. Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code 20 01 27*

Paint, inks, adhesives and resins containing dangerous substances

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / 1	14.2 D UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
ΙΑΤΑ	-	-	-	-	-	-

* Packing group

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

Use of this product requires dedicated training in work with polyurethane and epoxy products.

SEVESO - Categories / dangerous substances Not applicable.

^{**} Environmental hazards



Additional information

Not applicable.

Sources

The Management of Health and Safety at Work Regulations 1999.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH205, Contains epoxy constituents. May produce an allergic reaction.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H319, Causes serious eye irritation.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU 12 = Manufacture of plastics products, including compounding and conversion

SU 19 = Building and construction work

PROC 19 = Hand-mixing with intimate contact and only PPE available

PC 9b = Fillers, putties, plasters, modelling clay

PC 32 = Polymer Preparations and Compounds

AC 13 = Plastic articles

ERC 5 = Industrial use resulting in inclusion into or onto a matrix

ERC 8c = Wide dispersive indoor use resulting in inclusion into or onto a matrix

ERC 8f = Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development



PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail RRN = REACH Registration Number SCL = A specific concentration limit SVHC = Substances of Very High Concern STOT-RE = Specific Target Organ Toxicity - Repeated Exposure STOT-SE = Specific Target Organ Toxicity - Single Exposure TWA = Time weighted average UN = United Nations UVBC = Unknown or variable composition, complex reaction products or of biological materials VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law. The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The safety data sheet is validated by

H.A.B.

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en